

# Interface

SLIDE2

GEK.BCO.SLI.5100



USB RS485 Konverter  
GEK.CON.USB.RS41



SLIDE2

GEK.BCO.SLI.5100



NODE R08  
GEK.EBC.RNO.002



BASE R24  
GEK.BCO.RBA.004



# Verteiler

DMX Dimmer REG 4 Kanal  
230 V / max. 0.87 A / 200 W

GEK.DMX.RDI.2304



DMX

230 V AC

230 V AC



RLC

DMX Dimmer REG 4 Kanal  
12 bis 48 V DC / 5 A

GEK.DMX.RDI.2445



DMX

12-48 V DC

12-48 V DC



RLC



DMX Dimmer 4 Kanal  
24V DC/ 5A

GEK.DMX.SDI.2445



DMX

12-24 V DC



# Räume

## Lichtdimmung



### LEGENDE

	Versorgung Leitung 400/230V AC
	Abgang 230V AC/ X x Xmm <sup>2</sup>
	Abgang 24V DC/ X x Xmm <sup>2</sup>
	Versorgung 24V DC/ X x Xmm <sup>2</sup>
	Bus Leitung J-Y(STY)/ 2x2x0,8mm <sup>2</sup> G AC/ X x Xmm <sup>2</sup>
	RS485 Leitung/ 1x2x0,34 G
	Netzwerk/ CAT Xx
	v M-BUS 1x2x0,65mm <sup>2</sup> G